



A&A GORTRAC

A Division of A&A Manufacturing
www.gortrac.com
 Email: sales@gortrac.com
 Toll Free: 800-394-1547
 Fax: 262-786-3280

3-38 or circle 38 on card

g for Industrial er Challenging ations

line of quality seating solutions
 applications.

Custom fabricated, **made-to-order**
 seating fits your exact requirements.

- ◆ Wide variety of different sizes, seat heights, caster and arm options available
- ◆ Available with fabric, vinyl or polyurethane seats and backs
- ◆ Exceeds ANSI/BIFMA standards for safety and durability.
- ◆ Big & Tall models available
- ◆ Exclusive 12 year warranty

Call for a **FREE** copy
 of our new brochure

BEVCO

800) 864-2991
www.bevco.com

93-39 or circle 39 on card

nsically Safe ssure Gauges

Zone 0
 g
 S Sensor
 From
 e today!



Self-Propelled Trailer saves space



Space-saving self-propelled trailers can carry 100 tons-plus for in-plant use. Trailers are suited for congested, confined areas, and narrow intersecting aisles. Maneuverable trailers feature computerized independent steering, on-center rotating front axles, remote control operation, low-profile design, and on-board power generation. Units are powered by 480 V, 3 phase ac, LP gas engine driven generator. Shore power back-up option is offered as back-up power source and where virtually silent operation is desirable. Solid urethane wheels, 15 in. (381 mm) by 7.5 in. (191 mm) can operate on virtually any floor surface. **Doerfer Companies – Wheelift Systems Group:** 877-483-4700; 319-483-4700

www.ieninfo.com/11293-41 or circle 41 on card

Flame Detector receives IECEx approval

Approved for hazardous monitoring in industrial processes, flame detector models contain electronics within explosion-proof housings and provide 4-20 mA stepped output signal indicating detector status. Advanced

multispectrum IR Model FL4000H provides high false alarm immunity with widest field of view; Model FL3100H detects hydrocarbon and hydrogen fires by monitoring in UV/IR spectra; UV Model FL3101H detects fires and outputs alarm directly from detector while maintaining false alarm immunity; and IR Model FL3102 is highly immune to false alarms caused by lightning, arc welding, hot objects, and other sources of radiation. **General Monitors:** 800-330-9161; 949-581-4464. Tech Contact: Angela Saucedo

www.ieninfo.com/11293-42 or circle 42 on card



Hydraulic Cylinder gets jobs done faster, safer



Long-stroke RC Duo optimizes extension capabilities while minimizing retraction times. With heavy-duty pre-tensioned springs, high pressure 700 bar cylinders are available in capacities from 5 to 95 tons. GR2 dual bearing technology withstands lateral forces and dynamic loads, preventing galling and premature bearing failure. Long-stroke models, typically from 156 to 362 mm, incorporate double Golden Ring bearing protection, absorbing eccentric load stresses to protect cylinders against abrasion, overextending, or plunger blowouts and jamming. **Enerpac (Industrial Tools):** 800-433-2766

www.ieninfo.com/11293-44 or circle 44 on card

Clamp-Nut meets specialty fastener needs

Clamp-Nut is 3-piece fastener that includes inner sleeve, outer sleeve, and washer. Fastener has hardened surface in inner sleeve and washer that prevents galling. In addition, geometry of 3-piece

design allows fastener to safely bring increased mechanical tensioning to high loads. Standard Clamp-Nuts have load range that extends to 1.5 million pounds; unit sizes extend from 1-1/2 to 7 in. are standard with custom sizes available. It functions as mechanical tensioner while eliminating bolt over-stretching and highly stressed tensile pullers. Using driver and torque tool configuration, moving outer sleeve in clockwise motion causes inner sleeve to push upward, rising with bolt. This action provides accurate, gentle cold stretch without residual load loss. End result is pure tensile load and tensioned fastener. It comes in all thread forms, with low, standard, medium, and high temperature ratings available. **HYTORC, Div. UNEX Corporation:** 201-512-9500

www.ieninfo.com/11293-45 or circle 45 on card



Hard to Find Valve or Fitting

Spec it Right



The **CPV Mark VIII** line of stainless steel valves and tube fittings match your system requirements perfectly. Shutoff or regulating valves with traditional connections, or **Mark VIII** O-ring union ends for easy slip-in

IT'S MORE THAN A FLOW RACK...

